

```
/* Define default text */
#default {
color:#333;
}
```

Existing or new IDs can be combined with selectors in the style sheet to add further control. Let's say only the main <h2> on your page needs to be emphasized with a different color. This calls for a new rule where the selector is defined in the form `element#name`:

```
/* Adjust the color of h2 when used as a title */
h2#title {
color:#red;
}
```

Here the new rule will override the default <h2> colour with red (color: #red;) whenever an <h2> is identified with the id="title" in the HTML. Simply add the unique identifier to the page:

```
<h2 id="title">Title Of My Article</h2>
```

IDs should be reserved for unique, single-use elements such as the header, sidebar, the main navigation or the page footer. This lets you scan through your markup easily, as all ID attributes will denote unique content areas or special regions of the page. They also provide greater flexibility for a more complex CSS application. IDs must be avoided when there is more than one requirement for the same CSS rule. Do not use an ID for anything you will need to duplicate in the future, such as images, link styles, or paragraphs.

2.1.2 Class

A class selector can be employed any number of times on the same page, making it a very flexible method for applying CSS. A class lets an element belong to a group where common style rules are applied, or itself is a reusable object or style. The most common way of applying a class selector just like an ID selector is referencing it in the HTML using a `class="name"` attribute of an HTML element.

As with our ID example, the two classes are named `highlight` (for red text) and `default` (for dark gray text):

```
<p class="highlight">This paragraph has red text.</p>
<p class="default">This paragraph has dark gray text.</p>
```