

```
<p class="default">This also has dark gray text.</p>
```

Note that as the identifiers are classes, they can be used more than once, hence in this example two paragraphs have been identified as default. That would not be acceptable if IDs are used. The corresponding CSS uses a full stop (.) character to denote the rule is a reusable class. The full stop is combined with the class name to start the rule, followed by the property declarations:

```
/* Define highlight class */
.highlight {
color:#F00;
}
/* Define default class */
.default {
color:#333;
}
```

Classes are very useful when you want to have control over a number of elements. Consider the following drinks list.

```
<ul id="drinks">
<li class="alcohol">Beer</li>
<li class="alcohol">Spirits</li>
<li class="mixer">Cola</li>
<li class="mixer">Lemonade</li>
<li class="hot">Tea</li>
<li class="hot">Coffee</li>
</ul>
```

Note first that the unordered list () is given a unique ID. Thus, id="drinks" will not be used again on the page at any time, allowing that particular list to be styled uniquely. Note also that Beer and Spirits are within list elements defined with class="alcohol", Cola and Lemonade are within list elements defined with class="mixer", and finally Tea and Coffee are defined in list elements with class="hot". This allows each drinks group to be treated individually. The CSS declares that the default text for that list will be red, so any list items without a class attribute will default to red text:

```
/* Drinks list styling */
ul#drinks {
```