

3.5.1 border-style

The browser must first understand the style of border to be drawn before moving on to further border declarations. In other words, the style keyword is declared before any other property of the border. The property applies a defined style to one, several, or all borders. Values for border-style are none, dotted, dashed, solid, double, groove, ridge, inset and outset.

3.5.2 border-width

More specifically, in this section we will look at border-width, border-top-width, border-right-width, border-bottom-width, and border-left-width. These properties allow you to define the width of the element's edges one by one or all at once. Note that for a border-width value to be applied, a border-style must first be declared. Several keyword values are available here, as well as relative lengths.

The values for border-width include thin, medium, and thick, although caution is required as different browsers render these borders in different ways. Exactly how many pixels each browser will use varies. Note that if you define a border-style but not a border-width, the default value is medium.

3.5.3 border-color

Remember that, unless you declare the colour for the border, it will inherit colour from the element or parent element. As there is only one property for colour (border-color), multiple colours for different sides must be declared using shorthand:

```
/* Container for cantering all our content */
#container {
width: 400px;
margin: 10px auto 10px auto;
padding: 20px;
border-style: dashed dotted solid ridge;
border-top-width: thin;
border-right-width: 20px;
border-bottom-width: medium;
border-left-width: thick;
border-color: #000 #999 #333 #CCC;
}
```

This gives us borders from black (top) to lightest grey (left)