

```
border: 1px solid #000;  
padding:10px  
font: 12px Verdana, Arial, Sans-serif;  
line-height:150%;  
}  
  
h1, h2 {  
  letter-spacing:3px;  
}
```

It is worth noting that unlike line-height, negative values are allowed with letter-spacing, so something like 'letter-spacing: -0.5em' can be used to bunch up the characters if required. Using the em measurement will ensure that the spacing scales if the text size is later increased.

4.5 font-weight and font-style

The font-weight property is used to set the thickness of your text. Typically, the declaration is either normal or bold, but some browsers do support numeric values in increments of 100. That are 100 (lightest), 200, 300, 400 (same as normal), 700 (same as bold), 800, and 900 (even bolder!).

The default for font-style is normal, but typically you would use this property to declare any text that needs to be rendered in italics. Values are normal, italic, and oblique.

4.6 font-variant

The font-variant property is used to display the text in a small-caps font. Lowercase letters can be converted to uppercase letters, but all the letters in the small-caps have a smaller font size compared to the rest of the text. This is used to depict less important info such as stats, figures, or footer information. Possible values are simply normal or small-caps. Note that the browser will use a proper small-caps font if available; otherwise the effect is done computationally.

4.7 text-transform

This property is sort of an opposite of font-variant, where all characters can be rendered uppercase without reducing the font size. The 'text-transform:uppercase' declaration is especially useful for headings, where it is semantically incorrect to type using uppercase characters in the markup.