

```
</ul>  
</ul>
```

Load it in the browser window, and the default browser style sheet will use a disc bullet for the top level and a circle bullet for the second level. Because a hierarchy is suggested with the markup, it is possible to make significant style changes without applying IDs or classes. First, let's use CSS to change the colour of the second level list items.

```
/* Style top-level unordered list and contents */  
ul {  
  color:#000;  
}  
/* Style second-level unordered list and contents */  
ul li ul {  
  color:#666;  
}
```

Here the CSS selectors target the relevant list based on its relationship with another. Thus the first selector looks for the all `<ul>` elements it finds in the markup, and ensures the text is black, unless a declaration for a nested list says differently. Importantly, the second selector looks for any `<ul>` that is contained by one more above it, using the `ul li ul` descendant selector. In other words, the browser ignores the first `<ul>`, and any `<li>` elements inside it, but when it gets to the next `<ul>`, it will go to work and make its contents gray".

It becomes easy to define other custom values for each level. Building on our earlier example of assigning custom background images, the CSS can be used to target the second level of list elements specifically.

```
/* Style top-level unordered list and contents */  
ul {  
  color:#000;  
}  
/* Style second-level unordered list and contents */  
ul li ul {  
  list-style-type:none;  
  color:#666;  
}  
ul li ul li {
```