

approach to the Web since its early days and is easily recognizable for quickly analysing which links on a page the user has already visited

7.3 Template HTML markup

Let's start learning the rules by first setting up a new template, and then approach some simple CSS link declarations. Create a new template called `links.html` and paste the following markup into it:

```
<h2>Introducing the band</h2>
<p>To find out more about members of <a href="#">The Dead
Goods</a>, please select the appropriate person for a full
profile.</p>
<ul>
<li><a href="links.html"> </a></li>
<li><a href="#">John Lennon</a></li>
<li><a href="#">Jimi Hendrix</a></li>
<li><a href="#">Jeff Buckley</a></li>
<li><a href="#">Kurt Cobain</a></li>
<li><a href="#">Janis Joplin</a></li>
<li><a href="#">Keith Moon</a></li>
</ul>
```

Notice that the link to `#` links to the actual template created. This allows a visited link state to be available at all times which is essential for checking the visited link styling to be added shortly. Notice also that one link is placed in the opening paragraph, and the rest are correctly defined as list items. Save this template and load it in your browser. Notice that all links are the default dark blue, aside for the link to Judas Priest, which links to the page in view and so is a visited link, displayed in purple. Next, link to an external style sheet called `links.css`. Add declarations for the body selector, and also for the container div if you are using one.

7.4 Changing Link Colour (The different CSS states for a link)

Now let us add some simple CSS rules to take control of the links. This is done with the pseudo classes, `:link`, `:visited`, `:active`, and `:hover`. First, the pseudo class: `link` is combined with the `a` element selector (from the `<a href=...` part of the link markup), creating the selector `a:link`.

```
a:link {
```