

```
}  
a:active {  
color: #000;  
}
```

These default pseudo classes can be left alone; as all that is needed is a new descendant selector that applies extra declarations to these existing classes.

```
p a:link, p a:visited, p a:hover, p a:active {  
color:#F00;  
padding:2px;  
border:1px dashed #999;  
text-decoration:none;  
}
```

Here, the browser will look first for a paragraph, and then any link elements contained within. If one or more is found, the new declarations will be added to the existing pseudo classes. So, in addition to the colour declaration in the `:link` pseudo class, the new declarations (padding, border, and text-decoration) will be applied also.

Therefore, the same treatment can be given to links housed within another element, such as the list of links in the unordered list. To revisit the background images example from earlier in the chapter, the links in the list could be targeted as follows:

```
ul a:link {  
color:#F00;  
padding:0 15px 0 0;  
background:url(images/arrow.gif) no-repeat right center;  
}  
  
ul a:visited {  
color:#999;  
padding:0 15px 0 0;  
background:url(images/checkmark.gif) no-repeat right center;  
}
```

7.7 Transforming a navigation bar with links

We've seen how CSS can be used to transform a simple unordered list into a vertical navigation bar. It is useless if it doesn't actually link anywhere, so as discussed it is now time to make that simple list work as a navigation tool.