

except the fixed element, which holds its ground x pixels from the top, left, right, or bottom of the browser window.

8.5.4 Relative positioning

A relatively positioned element is relative to where it would normally be positioned statically. For example, if applied to a heading, you are defining where it should be relative to where the browser would normally put it.

8.5.5 Basic position properties and values

There are many possible properties to be used when positioning elements. For now, we will look into the following properties:

`position`

`top`

`left`

`bottom`

`right`

Other position-related properties will come into play later in the book, especially when you come to learning about layouts. For now, let's look at how position and associated properties affect basic elements.

Once the position of the element is defined, the top, left, bottom, and/or right properties are used to offset that element by the given values. All values can be defined using length, percentage, or auto. As stated, the offset is entirely dependent upon the value of the position property.

By applying CSS to the HTML example, it is easy to see how each position value works with the same top and left values. Note that for our position examples, the following HTML is used and the aim will be to control the position of the image () element.

```
<div id="container">
```

```
<h3> Judas Priest </h3>
```

```
<div class="image_float"></div>
```

```
<p>Can't actually play any instruments, and is just along
for the ride, supposedly as manager..</p>
```

```
</div>
```

The container div is given specific width and height values so that the browser window can be forced to scroll in order to see the effects of all position values.