

Now that you have created a new database to use, you have to tell WordPress about it. In the newly unzipped `wordpress/` folder, you'll find a file called `wp-config-sample.php`. Copy this file and rename it to `wp-config.php`.



Your gateway to WordPress

1. Replace `define('DB_NAME', 'putyourdbnamehere');` with `define('DB_NAME', 'wordpress');`.
2. Replace `define('DB_USER', 'usernamehere');` with `define('DB_USER', 'wpuser');`.
3. Replace `define('DB_PASSWORD', 'yourpasswordhere');` with `define('DB_PASSWORD', 'wppassword');`.
4. If your database host name is anything other than `localhost`, replace `define('DB_HOST', 'localhost');` with `define('DB_HOST', 'newdbhostname');` where `newdbhostname` is the name or IP address of the database server. This is optional and likely not required.

There are some additional optional settings in here as well. Notably, it is a good idea to change the `table_prefix` setting. It can be anything you want and defaults to `wp_`. Additionally, four other settings are defined, `AUTH_KEY`, `SECURE_AUTH_KEY`, `LOGGED_IN_KEY`, and `NONCE_KEY` that should all be changed to unique strings or phrases. They can be anything you want, and you'll never have to see them again. They simply help WordPress operate securely. You can auto-generate random settings for these four secure keys by visiting <https://api.wordpress.org/secret-key/1.1/> and copying and pasting the result on top of the exiting default settings. An example of randomly generated secure keys from <http://api.wordpress.org/secret-key/1.1/>