

API to determine how many “Diggs” an article has. Using conditional logic based on blogger-defined parameters (such as how many Diggs are required), it displays an interactive Digg This badge in a post.

WPTouch iPhone Theme

Given the popularity of the iPhone these days, iPhone-specific versions of a blog are in demand. The WPhone iPhone Theme plugin (<http://wordpress.org/extend/plugins/wptouch/>) uses jQuery to render a version of a WordPress blog that is formatted for the iPhone. The WPTouch iPhone Theme plugin renders a WordPress blog in an iPhone format. It uses jQuery.

4.8 Looking at theme styles

CSS order is not as important as JavaScript library order, but you do have to remember the “cascading” nature of Cascading Style Sheets. For example, with JavaScript, you encounter conflicts that have the potential of breaking a page if you load script.aculo.us before you load Prototype. This is why the `wp_enqueue_script()` function exists. Dependencies can be determined and scripts injected into the blog in the appropriate order, avoiding potentially site crippling side effects.

4.9 Queuing styles

While the `wp_enqueue_style()` function effectively does the same thing, CSS conflicts generally won’t cripple a site. However, the nature of CSS is to “cascade.” Styles cascade from a top-level hierarchy, and can be overridden later in a page execution. To this end, conflict is avoided using a similar syntax to `wp_enqueue_script()`. The first argument passed to `wp_enqueue_style()` must be a unique handler. The second argument should be the fully qualified URL to the stylesheet, while the third argument, which is completely optional, should be an array of dependencies (using the dependency handler name).

```
{
wp_enqueue_style('my-styles', WP_CONTENT_DIR . '/themes/
my-theme/style.
css');
wp_enqueue_style('ie-my-styles', WP_CONTENT_DIR . '/
themes/my-theme/
ie.css', array('my-styles'));
wp_print_styles();
```