

```
}
add_action('wp_enqueue_scripts', 'wpb_additional_css');
```

Using JavaScript to style elements

Sometimes it is necessary to use JavaScript to adjust styles on the fly. This is because some kind of event (hover, click, and so on) has occurred on a page after all the CSS files have been loaded and applied when the page initially loads. Fortunately, both the jQuery and Prototype frameworks discussed earlier in this chapter have ways to apply styling to an element after the page loads. For example, maybe you want to change the background color of a post when you hover over it. Using the default WordPress theme, you can write a function that adds some jQuery inside the <head> tag.

Using jQuery to change the hover background CSS of a post

```
<script type="text/JavaScript">
jQuery.noConflict();
jQuery(document).ready(function(){
jQuery('.entry').hover(
function() {
jQuery(this).css('background', '#eee');
},
function() {
jQuery(this).css('background', '#fff');
}
);
});
</script>
```

Using jQuery, a plugin can alter the defined style of an element. In this case, the background color of a post changes to a light grey when you hover over it. and styles can be deregistered if they're implemented with the style queue.

JavaScript can be used to alter CSS, creating a dynamic user experience. 

IMPORTANT

We've put the last chapter of this Fast Track on the Mindware DVD. Please read it from there. Write to editor@thinkdigit.com and tell us whether you prefer reading on screen or on paper. The way in which you get Fast Tracks in the future depends on this, so make sure to write in!