

initialization, this is 0 but it is incremented with every real SQL query.

last_query

The `last_query` property, despite its name, does not store the SQL of the most recent query at the time of execution. Instead, it stores the last dataset of the last query that was run.

col_info

If you want to retrieve specific information about a column in a database table, use `$wpdb->col_info`. The `col_info` property stores information such as column type, name, and so on.

queries

Sometimes there is a need to save queries. It's not common in the WordPress world given WordPress provides its own caching mechanism; however, the capability exists. The `queries` property is an array of saved queries that requires the constant `SAVEDQUERIES` to be defined as true. Because `queries` is a private property, you'll never actually use it directly but the database class itself will.

prefix

The `prefix` property is commonly used in WordPress and is set to the table prefix that you defined in your `wp-config.php` file. By default, this prefix is `wp_`, but it can be anything.

Plugin authors should also take note that `prefix` is a very important property. When creating queries within your functions for custom tables, never assume that table prefixes are `wp_`. Always use `$wpdb->prefix` instead. This ensures that your plugin is compatible with all possible WordPress installs, including WordPress MU blogs.

`ready`

Another internal (private) property, `ready`, will never be used outside of the database class itself. This property is set to false by default, and is internally set to true when queries are ready to be executed.

`posts`

The `posts` property holds the name of the posts table, including the table prefix. Most often, it is set to `wp_posts`.

In a WordPress data context, it is important to note that several types of content are included in the post table.