

|                                  | Name of Operand       | Symbol | Example | Result<br>a=0x03 b=0x11 |
|----------------------------------|-----------------------|--------|---------|-------------------------|
| Binary Operators                 | Greater than          | >      | a>b     | FALSE                   |
|                                  | Less than             | <      | a<b     | TRUE                    |
|                                  | Equal                 | ==     | a==b    | FALSE                   |
|                                  | Greater than or equal | >=     | a>=b    | FALSE                   |
|                                  | Less than or equal    | <=     | a<=b    | TRUE                    |
|                                  | Not equal             | !=     | a!=b    | TRUE                    |
|                                  | Logical AND           | &&     | a&& b   | TRUE                    |
|                                  | Logical OR            |        | a   b   | TRUE                    |
| Unary operators<br>(one operand) | Logical complement    | !      | !a      | FALSE                   |

```
Example for use of operators:
while (a!=b && a<=c) {
  ++a;
  --b;
  /* compute something more... */
}
```

4.2.9 Statements

Statements specify the flow of control as a program executes. In the absence of specific jump and selection statements, statements are executed sequentially in the order of appearance in the source code. C has a variety of mechanisms to control the flow of a program. These are listed below:

```
The if...then construct
if (logical expression) {
  ...statements...
}
```

If the logical expression is true then evaluate the statements between the braces. The following code sets RC1 if a is even.