

**Purpose:**

Used to provide a simple string replacement of the ID with the given text from this point of the program and on.

In the second form (a C macro) the local identifiers are matched up with similar identifiers in the text and they are replaced with text passed to the macro where it is used.

If the text contains a string of the form #idx then the result upon evaluation will be the parameter id concatenated with the string x.

If the text contains a string of the form #idx#idy then parameter idx is concatenated with parameter idy forming a new identifier.

**Examples:**

```
#define BITS 8
a=a+BITS;    //same as    a=a+8;
```

```
#define hi(x) (x<<4)
a=hi(a);     //same as    a=(a<<4);
```

**#INCLUDE**

|           |                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Syntax:   | #include <filename> or #include "filename"                                                                                                                                                                                                                                                                                                                                              |
| Elements: | filename is a valid PC filename. It may include normal drive and path information. A file with the extension ".encrypted" is a valid PC file. The standard compiler #include directive will accept files with this extension and decrypt them as they are read. This allows include files to be distributed without releasing the source code.                                          |
| Purpose:  | Text from the specified file is used at this point of the compilation. If a full path is not specified the compiler will use the list of directories specified for the project to search for the file. If the filename is in "" then the directory with the main source file is searched first. If the filename is in <> then the directory with the main source file is searched last. |
| Examples: | <pre>#include &lt;16C54.H&gt;  #include &lt;C:\INCLUDES\COMLIB\MYRS232.C&gt;</pre>                                                                                                                                                                                                                                                                                                      |