

10.5 JPasswordField

A JPasswordField is just another kind of JTextField, except it displays a string of asterisks in place of the text you're typing in. You can make an ActionListener listen to your JPasswordField object, but when it comes time to actually discover what is inside the actionPerformed, you must cast your(ActionEvent) object back into an object of type JPasswordField .

10.6 JButton

Constructors are:

- JButton()
- JButton(Icon)
- JButton(String)
- JButton(String, Icon)

It is initialized with a String that appears on it and can display an Icon. When the button isn't selected or pressed, you can change the Icon or see how it is currently set.

```
void setIcon(Icon)
Icon getIcon()
```

At run time, you can set or get the text displayed on the button.

```
void setText(String)
String getText()
```

Whenever the button is disabled (grayed out), you can change what icon it displays.

```
void setDisabledIcon(Icon)
Icon getDisabledIcon()
```

You can specify which Icon it will display when it is pressed.

```
void setPressedIcon(Icon)
Icon getPressedIcon()
```

A JButton can display a "mnemonic", or an underline that identifies the shortcut key.

```
void setMnemonic(int)
char getMnemonic()
```

This has two alternative overrides:

1. One accepts a char argument

```
setMnemonic(char mnemonic)
```

2. The other accepts an int constant of a type KeyEvent.VK_X

```
setMnemonic(int mnemonic)
```

(This one is preferred)