

```
void setActionCommand(String)
String getActionCommand(void)
```

`setActionCommand()`—this lets you define the action command string this button will generate when an event happens to it.

`getActionCommand()`—this is the command an Event Handler would use to discover the action command string. By default, a button's action command is set to the button text. We have used this method to process events.

When an event occurs, the button passes an `ActionEvent` object to the listener registered to listen for events on the button. The `ActionEvent` object has two commonly used methods:

- `getSource()` which returns the reference name of the object the event happened to, and
- `getActionCommand()` which “Returns the command string associated with this action.”

This usually means, “Return the String displayed on the button,” but you can set it to something more specific.

```
b1.setActionCommand("disable");
b3.setActionCommand("enable");
public void actionPerformed(ActionEvent e)
{
    if ( e.getActionCommand().equals("disable") )
    {
        b2.setEnabled(false);
        b1.setEnabled(false);
        b3.setEnabled(true);
    }
    else
    {
        b2.setEnabled(true);
        b1.setEnabled(true);
        b3.setEnabled(false);
    }
}
```

In fact, this is the preferred way to use this `setActionCommand()` method. Your program sets the Action Command String on an object that has an Action Listener. When the event happens, you can fine tune the result. Remember, when we call the method `getActionCommand()` of an