

```
action.add( enterNew );
action.add( printData );
action.add( exit );
bar.add( action );
```

Because menus and menu bars (also toolbars) are all subclasses of the `JComponent` class, they are all lightweight containers. Since they're containers, any type of component can be added to a Swing menu such as the icons you saw in the example.

10.10 JPopupMenu

A Popup Menu comes from anywhere on the GUI. On a Windows L&F, the 2nd mouse button triggers it. On a Unix Motif L&F, the 3rd mouse button triggers it. The `ActionListener` has to work hard to determine if the correct mouse button was pressed—meaning, if it was a valid “popup trigger”.

10.11 JToolBar

Unlike the menus, a `JToolBar` is not added with a specific method. Rather, the `JToolBar` is just added to the container like any other component. Further, Tool bars should be added to a container that contains an instance of the `BorderLayout`. In this `BorderLayout`, the `JToolBar` should be put in anywhere but the center of the `BorderLayout`.

To begin, the `JToolBar` is a container that can be oriented either horizontally or vertically. A Swing Tool Bar can float—meaning it can move around anywhere on the GUI the user desires. Using `JToolBar` methods:

- `add( Action )`, and
- `addSeparator`,

any type of component can be added to a `JToolBar`

This is a sample `JToolBar`. We just treat it as a component that gets buttons added to it. We can add any component to it, although the results don't always look the greatest unless we tweak the layout. If you drag a `JToolBar`, you can cause it to float into another side, where it will “stick” and attach itself. Otherwise, it can pop up in its own window.

10.12 JList

This class presents a GUI list of selectable objects. It supports three selection modes:

- single selection: you choose only one thing at a time.
- single interval selection: you choose several things in a row.