

methods in the `ListSelectionEvent` object. When you move through a list, this is the place you where you started. When you're making a selection, this is the place where you stopped.

With a `JList`, you have many alternative ways to discover what the user did:

`JList` Selection Properties

Property - Meaning

- `anchor` —the index that most recently began an interval selection.
- `lead` —the last index of the most recent selection interval.
- `maximum` —the highest index from the selected items.
- `minimum` —the lowest index from the selected items.

The `JList` component delegates three major jobs to other objects:

- data handling - to `ListModel`
- item selection - to `ListSelectionModel`
- cell rendering - to `ListCellRenderer`

All three of these are interfaces.

Example:

```
import javax.swing.*;
import javax.swing.event.*;
import java.awt.*;
import java.awt.event.*;

public class Test extends JApplet
{
    public void init()
    {
        Container c = getContentPane();
        c.setLayout(new FlowLayout());

        Object[] items = { "item one", "item two", "item three",
            "item four", "item five", "item six", "item seven", "item
            eight", "item nine", "item ten" };
        JList list = new JList( items );
        list.setVisibleRowCount( 7 );
        c.add( list );
    }
}
```

Instantiate an array of any `Object`. Then you instantiate the `JList` object with your array. You usually decide how many rows of the list you want to see at any one time. The default visible size is 8 rows.