

### 10.14 JTextArea

This familiar component can display multiple lines. It is basic in its function. For complex abilities, choose the `JEditorPane` and `JTextPane`. It also does not implement scrolling by itself. You can specify its word wrapping behavior.

```
JTextArea txt = new JTextArea();
txt.setLineWrap( true );
```

Properties maintained by the `JTextArea`:

- columns: `int`—the number of columns displayed
- line count: `int`—the number of lines of text contained in the text area.
- line wrap: `boolean`—determines whether or not lines of text are wrapped at the right edge of a text area.
- rows: `int`—the number of lines of text displayed in a text area.
- tabSize: `int`—number of characters inserted when the tab key is pressed.
- wrapStyleWord: `boolean`—when true, causes words to be wrapped on words. If false, wrap is on characters.

### 10.15 JEditorPane

Just like `JTextAreas`, these are capable of displaying multiple lines of editable text. Unlike text areas, `JEditorPanes` can display HTML and RTF formats.

```
JEditorPane editor = new JEditorPane();
editor.setPage( url );
```

Hyperlink events are fired when a mouse pressed event occurs over a hyperlink in an editor pane that is displaying an HTML document. Naturally, Swing defines a `HyperLinkListener` interface and `HyperLinkEvent` class that permits hyperlink events to be handled.

```
public abstract void
hyperlinkUpdate( HyperlinkEvent h )
```

The `HyperlinkEvent` object offers the following methods:

`HyperlinkEvent`:

- `public String getDescription()`
- `public HyperlinkEvent.EventType`  
`getEventType()`
- `public URL getURL()`

Example:

```
JEditorPane editor = new JEditorPane();
...
editor.addHyperlinkListener(
new HyperlinkListener()
```