

Range: -128 to 127

Again, like a short, a byte is only used under rare circumstances.

1.3.5 float

A float is defined as 4 bytes, no matter which operating system is used.

Range: approximately +/- 3.40282347E+38F (6-7 significant decimal digits) because there are so few decimal places available, float is not used all that often.

1.3.6 double

A double is defined as 8 bytes, no matter which operating system is used.

Range: approximately +/- 1.79769313486231570E+308 (15 significant decimal digits). This is the most common choice for any decimal. double is the default, not float, therefore, no special character is appended.

1.3.7 char

A char is defined as 2 bytes, irrespective of the operating system used. A char type always refers to a character in the Unicode encoding scheme. Approximately 65,536 characters can be represented. Single quotes denote a char constant. 'H' is a char constant. "H" is a String that contains a single character – it is not a char. This is a syntax error, and the compiler will give you an error.

1.3.8 boolean

A boolean type has only two values. In contrast to C/C++, in Java, 0 and 1 cannot stand in for true or false. A boolean type must be assigned the value of the constants true or false.

1.4. Java math operators

- Addition +
- Subtraction -
- Multiplication *
- Division /
- Modulus %

All are binary operators, i.e., they work with two numbers. They are executed according to the rules for operator precedence. (There is no operator for exponentiation in Java). Let us see some of the commonly overlooked things regarding Math operators in Java.