

```
// Calculate Compound Interest
import javax.swing.JOptionPane;
import java.text.DecimalFormat;
import javax.swing.JTextArea;
public class Interest
{
public static void main( String args[] )
{
double amount, principle = 1000.0, rate = 0.05;
DecimalFormat twoDig = new DecimalFormat( "0.00" );
JTextArea output = new JTextArea( 11, 20 );
output.append( "Year\tAmount on deposit\n" );
for( int year = 1; year <= 10; year++ )
{
amount = principle * Math.pow( 1.0 + rate, year );
output.append( year + "\t" + twoDig.format(amount) +
"\n");
} // end of for
JOptionPane.showMessageDialog( null, output,
"Compound Interest", JOptionPane.INFORMATION_MESSAGE);
System.exit( 0 );
} // end of main()
} // end of class Interest
```

2.4.4 Multiple-Selection structure

Once you start nesting many ‘if’s, it becomes a nuisance. Java—like C and C++ before it—provides the switch structure, which provides multiple selections. Unfortunately—in contrast to Visual Basic’s Select Case and even COBOL’s Evaluate—you cannot use any of type of argument in the switch statement other than an integer.

```
int x = 0;
switch( x )
{
case 1:
do stuff;
break;
case 2:
do stuff;
```