

```
}
```

This is the first Constructor. Notice that it takes no arguments, but it still sets the instance variables for hour, minute and second to consistent initial values of zero.

```
public Time2 ()
{
    setTime( 0, 0, 0 );
}
public Time2( int h, int m, int s )
{
    setTime( h, m, s );
}
```

These are the first two Constructors. The second one overrides the first. The second Constructor takes arguments. It still calls the setTime() method so it can validate the data.

Accessors are a public method to display private variables. The access to private member variables is provided through the Accessor, or “gets” methods. This allows the designer of the class to control how and anyone can access the private data. They are also called Query methods. Public methods used to change private variables. Mutators “set” private data. The designer can filter the incoming data and ensure it is correct before it is used to change the private data. This permits the data to be correctly validated before it is used to update the member variables.

- You were sitting in your Ferrari in your driveway.
- Next door, your plumber neighbor was sitting in her Ferrari.
- If you wanted to refer to your neighbor’s Ferrari, you would naturally say “Jane’s Ferrari....”
- Likewise, it would be perfectly natural for you to refer to the car you were sitting in as “this Ferrari....”

4.10 Finalizer methods

We know that the Constructor method is used to instantiate and initialise an object in memory. To avoid the problem called a “memory leak” one which plagues the C/C++ environment it is beneficial to have an anti-Constructor method. Such methods exist. They are called Finalizers, and they control the orderly removal of objects from memory. When an object has gone out of scope, the finalizer executes automatically to clean up (release) used system resources. When there are no longer any references to an object, it is eligible