

two, our request prevails.

43

6.5 Character class

Most methods in the Class Character are Static. Most of these methods take a character argument. They perform either a test or a manipulation on that argument.

method isDefined() seeks to know if the character that is provided as an argument is defined in the Unicode character set.

```
int x = "}";  
Character.isDefined( x );  
true means the character is defined.
```

This method tries to determine if a character is an alphabetic letter of any language in the Unicode character set or if it is not.

```
int x = "t";  
Character.isLetter( x );  
true means the character is a letter.
```

This method tries to determine if a character is a digit.

```
int x = "3";  
Character.isLetter( x );  
true means the character is a digit.
```

6.6 StringTokenizer class

The StringTokenizer class is a tremendously useful and tricky class that can be used to do things like break a String up into words. What we call a “word”, the computer knows as a “Token” or a unit of a String. You will find this term is used commonly in other languages also.

The item used to decide where one token ends and another begins is called the delimiter. Commonly, you choose the delimiter to be a space, tab or newline. Although these are the common delimiters, you get to choose what you want to use for a delimiter. In fact, a token can be many characters, not just one.

In fact, you can change the delimiter every time you call a method of the StringTokenizer class object. When you use an object of class StringTokenizer, there is one primary decision that has to be made. If the returnTokens flag is false, then the delimiter characters only separate other tokens. If the returnTokens flag is true, then the delimiter characters are themselves tokens. Remember, a token doesn’t have to be just one character,