

Debug.Locals	CTRL-ALT-V, L	Displays the Locals window to view the variables and their values for the currently selected procedure in the stack frame.
Debug.Memory1	CTRL-ALT-M, 1	Displays the Memory 1 window to view memory in the process being debugged. This is particularly useful when you do not have debugging symbols available for the code you are looking at. It is also helpful for looking at large buffers, strings, and other data that does not display clearly in the Watch or Variables window.
Debug.Memory2	CTRL-ALT-M, 2	Displays the Memory 2 window.
Debug.Memory3	CTRL-ALT-M, 3	Displays the Memory 3 window.
Debug.Memory4	CTRL-ALT-M, 4	Displays the Memory 4 window.
Debug.Modules	CTRL-ALT-U	Displays the Modules window, which allows you to view the .dll or .exe files loaded by the program. In multiprocess debugging, you can right-click and select Show Modules for all programs.
Debug.NewBreakpoint	CTRL-B	Opens the New Breakpoint dialog.
Debug.QuickWatch	CTRL-ALT-Q	Displays the Quick Watch dialog with the current value of the selected expression. Available only in break mode. Use this command to check the current value of a variable, property, or other expression for which you have not defined a watch expression.
Debug.Registers	CTRL-ALT-G	Displays the Registers window, which displays CPU register contents.
Debug.Restart	CTRL-SHIFT-F5	Terminates the current debugging session, rebuilds if necessary, and then starts a new debugging session. Available in break and run modes.
Debug.RunningDocuments	CTRL-ALT-N	Displays the Running Documents window that displays the set of HTML documents that you are in the process of debugging. Available in break and run modes.
Debug.RunToCursor	CTRL-F10	Starts or resumes execution of your code and then halts execution when it reaches the selected statement. This starts the debugger if it is not already running.
Debug.SetNextStatement	CTRL-SHIFT-F10	Sets the execution point to the line of code you choose.
Debug.ShowNextStatement	ALT-NUM *	Highlights the next statement to be executed.
Debug.Start	F5	If not currently debugging, this runs the startup project or projects and attaches the debugger. If in break mode, this allows execution to continue (i.e., it returns to run mode).
Debug.StartWithoutDebugging	CTRL-F5	Runs the code without invoking the debugger. For console applications, this also arranges for the console window to stay open with a "Press any key to continue" prompt when the program finishes.
Debug.StepInto	F11	Executes code one statement at a time, tracing execution into function calls.
Debug.StepOut	SHIFT-F11	Executes the remaining lines of a function in which the current execution point lies.
Debug.StepOver	F10	Executes the next line of code but does not step into any function calls.
Debug.StopDebugging	SHIFT-F5	Available in break and run modes, this terminates the debugging session.