

```
1. <?xml version="1.0" encoding="utf-8"?>
2. <resources>
3.     <string name="hello">Hello World, HelloWorld!</string>
4.     <string name="app_name">Hello, World!!!</string>
5. </resources>
```

2.6 R File

R file in the /gen folder connects resources to Java, and is automatically generated. It is recreated with every change in the res directory. Eclipse automatically handles this file.

2.7 Java source code

Java Source code drives everything. This is what gets converted into a Dalvik executable file to run your application. Your code looks like this:

```
1 package com.thinkdigit.android;
2 import android.app.Activity;
3 import android.os.Bundle;
4 public class HelloWorld extends Activity {
5 /** Called when the activity is first created. */
6 @Override
7 public void onCreate(Bundle savedInstanceState) {
8 super.onCreate(savedInstanceState);
9 }}
```

This is where you add your own bit of code for additional operations.

2.8 Emulator

An Emulator runs your application as a virtual layer on another host so that you don't have to spare an Android phone to test your apps. It runs the same base code as an actual device.

A true emulator based on QEMU (type of a processor emulator covered under GNU GPL version 2) is shipped along with Android SDK. It acts like a hosted virtual machine monitor. We'll now create an Android Virtual Device, or an AVD to use this emulator. Start the tool called Android SDK and AVD Manager from the Eclipse Window menu.

Clicking on New opens a 'Create new Android Virtual Device (AVD)' window. Specify the parameters for your new AVD.

- **Name:** Any English name you choose
- **Target:** Version of Android you want installed on this AVD. If you don't