

class and override the `onCreate()` method. Activities go through a certain state machine, which is its life cycle. The transition in state we want to bring is to override the `onCreate()` method invoked by `ActivityManager` of the system when the activity was created. The `onCreate()` method will set up the button to respond to clicks, and further connect it to the cloud. It takes a `Bundle` (small amount of data passed into an activity through the intent that triggered it) as a parameter, which is limited to basic data types; complex ones need to be encoded. To override a method, first call the original parent method, hence the `super.onCreate()` call. After subclassing the framework's class, override the appropriate method and call `super's` method in it. The code now does the same thing as the original class, but now we have a placeholder to add our own code.

We typically start by writing some Java code that opens up our XML layout file, parses it, and for every element in the XML file, it creates a corresponding Java object in the memory space. The code sets every attribute of an XML element in our Java object, i.e. inflates from XML are done by adding `setContentView(R.layout.status)`;

`R` class is a set of automatically generated pointers which connects Java to XML and other resources in the `/res` folder. `R.layout.status` points to `status.xml` file. The `setContentView()` method reads the XML file, parses it, creates appropriate Java objects, sets object properties, sets up parent-child relationships, and in all inflates the entire view.

Not only user-created objects alone, but Android's user interface objects also define methods and respond to external stimulus.

Hence, to execute a `Button` click action, define an `onClick()` method and put the code you want to execute. In addition to this, you must run `setOnClickListener` method on the `Button`. This can be passed as an argument to the listener as the object is where `onClick()` is defined.

Your code for `StatusActivity.java` should look like:

```
1 package com.thinkdigit.envy;
2 import winterwell.jtwitter.Twitter;
3 import android.app.Activity;
4 import android.os.Bundle;
5 import android.util.Log;
6 import android.view.View;
7 import android.view.View.OnClickListener;
8 import android.widget.Button;
9 import android.widget.EditText;
```