

```
10 public class StatusActivity extends Activity implements
    OnClickListener{
11     private static final String TAG = "StatusActivity";
12     EditText editText;
13     Button updateButton;
14     Twitter twitter;
15     /** called when the activity is first created. */
16     @Override
17     public void onCreate(Bundle savedInstanceState) {
18         super.onCreate(savedInstanceState);
19         setContentView(R.layout.status);
20         editText= (EditText) findViewById(R.id.editText);
21         updateButton=(Button) findViewById(R.id.buttonUpdate);
22         updateButton.setOnClickListener(this);
23         twitter = new Twitter("username", "password");
24         twitter.setAPIRootUrl("http://envy.thinkdigit.com/api");
25         // Button Click
26         public void onClick(View v){
27             twitter.setStatus(editText.getText().toString());
28             Log.d(TAG, "onClicked");
29         }}
```

3.4.2 Compiling code

Eclipse builds every time you save your project, so remember to save your files after writing every block of code. Due to interdependency between Java and XML, transition from one file to another becomes more difficult with the current file broken, and makes it even more difficult to find errors. Clicking on the red 'x' marks generates possible solutions. This is like spell check in any word processor.

3.4.3 Adding libraries

We'll take a closer look at the `jtwitter.jar` library that lets us implement Twitter status updates. The connection happens through a series of web service calls. Winterwell Associates' `jtwitter.jar` library contains a simple Java class. This class interacts with online services, hence abstracting all the intricacies of network calls and data transfer.

Download the library from <http://www.winterwell.com/software/jtwitter.php> and insert it in your Eclipse project. Do this by clicking Alt + Enter with your