

```
51 new PostToTwitter().execute(status);
52 Log.d(TAG, "onClicked");}}
```

Now, when the user clicks on the Update button, the activity will create a separate thread using `AsyncTask` and place the network operations on that thread. Upon completion, `AsyncTask` will update the main UI thread by popping up a toast message telling the user about the success or failure of the update. This makes the application more responsive and the ANR status is eliminated.

3.8 Other UI events

Till now we've seen the handling of click events. Now we'll show how to implement the following operations:

`TextWatcher` watches the changes in the text field. We'll use another `TextView` on our layout to indicate the number of characters available. We'll also implement a color shift from green to yellow to red as the user reaches the maximum limit of 140 characters.

The code will now look like the following:

3.8.1 Status.xml

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <!-- Main Layout of StatusActivity -->
3 <LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
4     android:orientation="vertical"
5     android:layout_width="fill_parent"
6     android:layout_height="fill_parent"
7 >
8 <!-- Title text view -->
9 <TextView
10     android:layout_width="fill_parent"
11     android:layout_height="wrap_content"
12     android:gravity="center"
13     android:textSize="30sp"
14     android:layout_margin="10dp"
15     android:text="@string/titleStatus"
16 />
17 <!-- Text Counter text view -->
18 <TextView
```