

```
BaseballWatch.class));
    // Stop a service using the service name.
    stopService(new Intent(this, service.getClass()));
    // Stop a service explicitly.
    try {
        Class serviceClass = Class.forName(service.getClassName());
        stopService(new Intent(this, serviceClass));
    } catch (ClassNotFoundException e) {}
```

If `startService` is called on a Service that's already running, the Service's `onStartCommand` handler will be executed again. Calls to `startService` do not nest, so a single call to `stopService` will terminate it no matter how many times `startService` has been called.

5.3 Binding Activities to Services

When an Activity is bound to a Service, it maintains a reference to the Service instance itself, enabling you to make method calls on the running Service as you would on any other instantiated class.

Binding is available for Activities that would benefit from a more detailed interface with a Service. To support binding for a Service, implement the `onBind` method:

```
private final IBinder binder = new MyBinder();

@Override
public IBinder onBind(Intent intent) {
    return binder;
}

public class MyBinder extends Binder {
    MyService getService() {
        return MyService.this;
    }
}
```

The connection between the Service and Activity is represented as a `ServiceConnection`. You'll need to implement a new `ServiceConnection`, overriding the `onServiceConnected` and `onServiceDisconnected` methods to get a reference to the Service instance once a connection has been established:

```
// Reference to the service
private MyService serviceBinder;
```