

Once your Service no longer requires foreground priority you can move it back to the background, and optionally remove the ongoing Notification using the `stopForeground` method. The Notification will be automatically cancelled if your Service stops or is terminated.

```
// Move to the background and remove the Notification
stopForeground(true);
```

5.5 Using Background Threads

To ensure that your applications remain responsive, it's good practice to move all slow, time-consuming operations off the main application thread and onto a child thread.

Android provides two alternatives for backgrounding your processing. The `AsyncTask` class lets you define an operation to be performed in the background, then provides event handlers you can use to monitor progress and post the results on the GUI thread. Alternatively, you can implement your own `Threads` and use the `Handler` class to synchronize with the GUI thread before updating the UI. Both techniques are described in this section.

5.5.1 Using `AsyncTask` to Run Asynchronous Tasks

The `AsyncTask` class offers a simple, convenient mechanism for moving your time-consuming operations onto a background thread. It offers the convenience of event handlers synchronized with the GUI thread to let you update Views and other UI elements to report progress or publish results when your task is complete.

`AsyncTask` handles all of the Thread creation, management and synchronization, enabling you to create an asynchronous task consisting of processing to be done in the background and a UI update to be performed when processing is complete.

Creating a new Asynchronous Task

To create a new asynchronous task, you need to extend `AsyncTask`. Your implementation should specify the classes used for input parameters on the `execute` method, the progress-reporting values and the result values in the following format:

```
AsyncTask<[Input Parameter Type], [Progress Report Type],
[Result Type]>
```

If you don't need or want to take input parameters, update progress, or report a final result, simply specify `Void` for any or all of the types required.