

```
        backgroundThreadProcessing();
    }
};

// Method which does some processing in the background.
private void backgroundThreadProcessing() {
    [ ... Time consuming operations ... ]
    handler.post(doUpdateGUI);
}

// Runnable that executes the update GUI method.
private Runnable doUpdateGUI = new Runnable() {
    public void run() {
        updateGUI();
    }
};

private void updateGUI() {
    [ ... Open a dialog or modify a GUI element ... ]
}
```

The Handler class also lets you delay posts or execute them at a specific time, using the `postDelayed` and `postAtTime` methods, respectively.

5.6 Toast

Toasts are transient dialog boxes that remain visible for only a few seconds before fading out. Toasts don't steal focus and are non-modal, so they don't interrupt the active application. These dialog boxes are perfect for informing your users of events without forcing them to open an Activity or read a Notification. They provide an ideal mechanism for alerting users to events occurring in background Services without interrupting foreground applications.

The Toast class includes a static `makeText` method that creates a standard Toast display window. Pass the application Context, the text message to display and the length of time to display it (`LENGTH_SHORT` or `LENGTH_LONG`) to the `makeText` method to construct a new Toast. Once a Toast has been created, display it by calling `show`.

```
Context context = getApplicationContext();
String msg = "To health and happiness!";
```