

```

        Object[] pdus = (Object[]) bundle.get("pdus");
        SmsMessage[] messages = new SmsMessage[pdus.length];
        for (int i = 0; i < pdus.length; i++)
            messages[i] = SmsMessage.createFromPdu((byte[])
pdus[i]);
    }

```

Each `SmsMessage` contains the SMS message details, including the originating address (phone number), time stamp and the message body.

Let's see a Broadcast Receiver implementation whose `onReceive` handler checks incoming SMS texts that start with the string `@echo`, and then sends the same text back to the number that sent it.

```

public class IncomingSMSReceiver extends BroadcastReceiver
{
    private static final String queryString = "@echo";
    private static final String SMS_RECEIVED =
        "android.provider.Telephony.SMS_RECEIVED";

    public void onReceive(Context _context, Intent _intent) {
        if (_intent.getAction().equals(SMS_RECEIVED)) {
            SmsManager sms = SmsManager.getDefault();

            Bundle bundle = _intent.getExtras();
            if (bundle != null) {
                Object[] pdus = (Object[]) bundle.get("pdus");
                SmsMessage[] messages = new SmsMessage[pdus.
length];

                for (int i = 0; i < pdus.length; i++)
                    messages[i] = SmsMessage.createFromPdu((byte[])
pdus[i]);

                for (SmsMessage message : messages) {
                    String msg = message.getMessageBody();
                    String to = message.getOriginatingAddress();

                    if (msg.toLowerCase().startsWith(queryString)) {
                        String out = msg.substring(queryString.
length());

                        sms.sendTextMessage(to, null, out, null, null);

```