

```

    }
    else {
        if (currentAddress.getPostalCode() != null)
            sb.append(currentAddress.getPostalCode());
    }
}
} catch (IOException e) {}

ArrayList<String> locationMsgs =
sms.divideMessage(sb.toString());
for (String locationMsg : locationMsgs)
    sms.sendTextMessage(_to, null, locationMsg, null, null);
}
}

```

13. In emergencies, it's important that messages get through. Improve the robustness of the application by including auto-retry functionality. Monitor the success of your SMS transmissions so that you can rebroadcast a message if it doesn't successfully send.

- a. Start by creating a new public static String in the Emergency Responder Activity to be used as a local "SMS Sent" action.

```

public static final String SENT_SMS =
    "com.paad.emergencyresponder.SMS_SENT";

```

- b. Update the respond method to include a new PendingIntent that broadcasts the action created in the previous step when the SMS transmission has completed. The packaged Intent should include the intended recipient's number as an extra.

```

public void respond(String _to, String _response,
                    boolean _includeLocation) {
    // Remove the target from the list of people we
    // need to respond to.
    lock.lock();
    requesters.remove(_to);
    aa.notifyDataSetChanged();
    lock.unlock();

    SmsManager sms = SmsManager.getDefault();

    Intent intent = new Intent(SENT_SMS);

```