

```

intent.putExtra("recipient", _to);

PendingIntent sent =
PendingIntent.getBroadcast(getApplicationContext(),
                                0, intent, 0);

// Send the message
sms.sendTextMessage(_to, null, _response, sent, null);

StringBuilder sb = new StringBuilder();

if (_includeLocation) {
[ ... existing respond method that finds the location ... ]
ArrayList<String> locationMsgs =
    sms.divideMessage(sb.toString());
for (String locationMsg : locationMsgs)
    sms.sendTextMessage(_to, null, locationMsg, sentIntent,
null);
}
}

```

- c. Then implement a new Broadcast Receiver to listen for this Broadcast Intent. Override its `onReceive` handler to confirm that the SMS was successfully delivered; if it wasn't, then put the intended recipient back onto the requester `ArrayList`.

```

private BroadcastReceiver attemptedDeliveryReceiver = new
BroadcastReceiver() {
    @Override
    public void onReceive(Context _context, Intent _intent) {
        if (_intent.getAction().equals(SENT_SMS)) {
            if (getResultCode() != Activity.RESULT_OK) {
                String recipient = _intent.getStringExtra("recipient");
                requestReceived(recipient);
            }
        }
    }
};

```

- d. Finally, register the new Broadcast Receiver by extending the `onCreate`