

- ▶ Click **Start > All Programs > MeeGo 1.1 SDK > Qt Creator.**
- ▶ Select Create Project
- ▶ Select Empty Qt project
- ▶ Select the directory you want to create the project in.
- ▶ And you are done!

Your first Qt Program - Hello Digit

- ▶ When you create a new Qt project, you get the following screen
- ▶ Right click on hello and add new C++ source file
- ▶ Type this simple code
 - 1 `#include <QApplication>`
 - 2 `#include <QLabel>`
 - 3 `int main(int argc, char *argv[])`
 - 4 `{`
 - 5 `QApplication app(argc, argv);`
 - 6 `QLabel *label = new QLabel("Hello Qt!");`
 - 7 `label->show();`
 - 8 `return app.exec();`
 - 9 `}`

Interpretation:

The first two lines include the definitions of the `QApplication` and `QLabel` classes. For every Qt class, there is a header file with the same name (and capitalization) as the class that contains the class's definition.

The fifth line creates a `QApplication` object to manage application-wide resources. The `QApplication` constructor requires `argc` and `argv` because Qt supports a few command-line arguments of its own.

The next line creates a `QLabel` widget that displays "Hello Qt!". In Qt and Unix terminology, a widget is a visual element in a user interface. The term stems from "window gadget" and is the equivalent of both "control" and "container" in Windows terminology. Buttons, menus, scroll bars, and frames are all examples of widgets. Widgets can contain other widgets; for example, an application window is usually a widget that contains a `QMenuBar`, a few `QToolBars`, a `QStatusBar`, and some other widgets. Most applications use a `QMainWindow` or a `QDialog` as the application window, but Qt is so flexible that any widget can be a window. In this example, the