

```

• 17 connect(findButton, SIGNAL(clicked()),
• 18         this, SLOT(findClicked()));
• 19 connect(closeButton, SIGNAL(clicked()),
• 20         this, SLOT(close()));

```

The private slot `enableFindButton(const QString &)` is called whenever the text in the line editor changes. The private slot `findClicked()` is called when the user clicks the Find button. The dialog closes itself when the user clicks Close. The `close()` slot is inherited from `QWidget`, and its default behavior is to hide the widget from view (without deleting it). We will look at the code for the `enableFindButton()` and `findClicked()` slots later on.

Since `QObject` is one of `FindDialog`'s ancestors, we can omit the `QObject::` prefix in front of the `connect()` calls.

```

• 21 QHBoxLayout *topLeftLayout = new QHBoxLayout;
• 22 topLeftLayout->addWidget(label);
• 23 topLeftLayout->addWidget(lineEdit);
•
• 24 QVBoxLayout *leftLayout = new QVBoxLayout;
• 25 leftLayout->addLayout(topLeftLayout);
• 26 leftLayout->addWidget(caseCheckBox);
• 27 leftLayout->addWidget(backwardCheckBox);
•
• 28 QVBoxLayout *rightLayout = new QVBoxLayout;
• 29 rightLayout->addWidget(findButton);
• 30 rightLayout->addWidget(closeButton);
• 31 rightLayout->addStretch();
•
• 32 QHBoxLayout *mainLayout = new QHBoxLayout;
• 33 mainLayout->addLayout(leftLayout);
• 34 mainLayout->addLayout(rightLayout);
• 35 setLayout(mainLayout);

```

Next, we lay out the child widgets using layout managers. Layouts can contain both widgets and other layouts. By nesting `QHBoxLayouts`, `QVBoxLayouts`, and `QGridLayouts` in various combinations, it is possible to build very sophisticated dialogs.