

position belongs to the Text element so we set the position inside its definition. Note that we separate different QML statements on the same line with a semi-colon, or we could have simply put each statement on a new line

```
•   Text {
•       text: "<h2>Hello Digit</h2>"; color: "green"
•       x: 100; y:100
•   }
```

Not only did we reposition the text, but the text was altered by adding HTML tags to change the font size. The text color was also changed from the default black to dark green by using a standard string for the color's SVG name.

We could also have used a hexadecimal string for the RGB (red-green-blue, as #rrggb) values of the color similar to the method used in HTML,

```
•   Text {
•       text: "<h1>Hello Digit</h1>"
•       color: "#882200"
•       x: 100; y: 100
•   }
```

All of these changes occurred within the Text object which is the scope of these property changes.

Other objects may use the information but it belongs to the element where the property has been defined.

Images

To add an image to our little application we use the Image element. An Image uses a path to an image file, and has properties to control the aspect ratio, the image size, to tile the area amongst others. The source of the image, the path to the file, is a URL. Therefore the file can be local or it can be remote.

```
•   Image {
•       source: "img/digit.gif"
•   }
```

This displays the image, as we would expect, at the top left of the window. The position of the default x = 0, y = 0 coordinate. The example here uses a PNG file, but it could have been one of various supported formats, including JPG and GIF.

Let us reposition the image and enlarge it. Place it at the same 'x' offset as the "Hello world again" text, but put it another 50 pixels below the text, also make it 150 by 150 pixels in size,