

```

•         color: "#002288"
•         x: 100; y: 100
•     }
•     Image {
•         source: "img/digit.gif"
•         x: 100; y: 150
•         width: 167; height: 36
•     }
•     color: "lightgray"
• }

```

The result is still quite simple

## Anchors: Aligning Elements

Using absolute positioning, such as saying  $x = 100$  and  $y = 150$ , works well until the user or developer stretches or increases the size of the window. Then the positions need to be recalculated. What would be nice would be a relative means of positioning of objects in a window or rectangle. For example, we want to place an image at the bottom of a rectangle, we would like to specify the image's location as the 'bottom of the window', not a specific coordinate. We can do this with the anchors property, which objects inherit from Item.

The anchors property is really a property group. It is a collection of related properties. It has properties within it which can be used by means of the dot notation.

The dot notation uses object ids and property names to use a particular object or property. Say I have a rectangle `r1`, which contains a rectangle `r2`, which contains an Item `item1`, which has an 'x' property I want to change. I just use the dot notation to identify it: `r1.r2.item1.x`

If we want to position an image at the bottom of the rectangle it is inside. I have to specify that the bottom of the image is also at the bottom of the rectangle

```

• import QtQuick 1.0
•
• Rectangle {
•     id: myWin
•     width: 500

```