

```

•         id: image2
•         source: "img/digit.gif"
•         width: 167; height: 36
•         x: (mainRec.width - 100)/2; y: (mainRec.height -
100)/2
•         z: 2
•     }
• }

```

We will add to 'image1' a `SequentialAnimation` from `x = 20` to the target of `x = 450`. The 'from' values will be used because we will be repeating the animation, so the object needs to know where the original position is, both `x` and `y`. The `SequentialAnimation` of `x` will set it to repeat by indicating that the number of animation loops is infinite, indicating an endless cycle. Also there will be a `NumberAnimation` to vary the numeric property between the `x` values and over a given duration. After the `NumberAnimation` there will be a `PauseAnimation` that will pause the animation for 500 milliseconds (half a second) simply for the visual effect.

```

•     Image {
•         id: image1
•         source: "img/digit.gif"
•         x: 20; y: 20 ; z: 1
•         width: 167; height: 36
•         SequentialAnimation on x {
•             loops: Animation.Infinite
•             NumberAnimation {
•                 from: 20; to: 450
•                 easing.type: "InOutQuad"; duration: 2000
•             }
•             PauseAnimation { duration: 500 }
•         }
•     }

```

A similar block of code is written for the animation of the 'y' value of the position.

We will also animate the scale of the object, so as it goes from top left to bottom right of the window it will become smaller until about midway, and then become larger.