

- ▶ Now, you can copy any background files into `/usr/share/backgrounds`. If you want them to appear in the list of wallpapers, you can edit the file `/usr/share/gnome-background-properties/ubuntu-wallpapers.xml`. If you are doing so, use the ‘nano’ command line editor. It’s best not to use a text editor from the parent working environment. You can also edit the `/usr/share/gconf/defaults/16_ubuntu-wallpapers` file to change the default wallpaper.
- ▶ Now run `sudo nano edit/usr/share/initramfs-tools/scripts/casper` if you want to edit the live cd username. Do so from outside the chroot jail. It should be set to ‘casper’ change that to something you want. Be careful though. Do not edit anything you do not understand. You might mess up.
- ▶ In case you have installed anything which would have added modules to the kernel, you need to rebuild the initramfs image. Do so by exiting the chroot and rebuilding the initramfs:

- `sudo chroot edit`
- `mkinitramfs -o /initrd.lz 2.6.38-8-generic`

Remember, the version above is for the Ubuntu Natty. If you are using some other Linux kernel for the ISO, the same kernel version should be used above.

- ▶ Now exit the chroot (type ‘exit’ and hit enter) and move the resulting ramfs image to the right directory where it will be available when booting:

- `exit`
- `mv edit/initrd.lz extract-cd/casper/`

- ▶ Now you should remove the machine id file so that the system may become reusable (should be done from inside the chroot jail – `sudo chroot edit`):

- `rm /var/lib/dbus/machine-id`

- ▶ Also undo the diversion which we did earlier for package installation:

- `rm /sbin/initctl`
- `dpkg-divert --rename --remove /sbin/initctl`

- ▶ Now, unmount the virtual file systems which were mounted:

- `umount /proc || umount -lf /proc`