

```
vorbis"" />
```

- `<source src="movie.mp4" type='video/mp4; codecs="avc1.42E01E, mp4a.40.2"' />`
- `<source src="movie.ogv" type='video/ogg; codecs="theora, vorbis"' />`
- Video tag not supported. Download the video `<a href="movie.webm">here</a>`.
- `<video>`

Encoding

There are many free and paid video encoders available that will help you get your video into the appropriate formats. Check out <http://diveintohtml5.org/video.html#webm-cli> for some good tools you can use.

Attributes (HTML)

▶ AUTOPLAY

The video tag has an attribute that allows the video to play when the page loads.

- `<video src="abc.mov" autoplay>`
- `</video>`

▶ DOWNLOAD

If the browser doesn't know what to do with video tag, or if there is a display error, you can offer a download to the video instead:

▶ AUTOBUFFER

Autobuffer attribute is used when autoplay is not used but the page/site owner thinks the video will be watched at some point. The video is downloaded in the background, so when the user starts the video, it will be able to play at least some of the content. If both autoplay and autobuffer are used, then autobuffer is ignored.

▶ POSTER

You can use the poster attribute to display a frame of the video (as a .jpg, .png, whatever), in case the video doesn't load for some reason.

▶ CONTROLS

Adding this attribute means you can use your own play/pause/etc buttons for your video. It is used to indicate that instead of building our custom controls we want the browser to render one automatically for us.