

Integration

As we said in the introduction, the main advantage of the video tag being a member of the HTML5 family, is the integration with the other layers of web development stack. Let us take a look at the kind of interesting stuff you can do

▶ VIDEO + other HTML

All the common HTML attributes, we described in the previous section, can be used in the video player.

```

• <video poster="star.png" autoplay loop controls tab-
  index="0">
•   <source src="movie.webm" type='video/webm; codecs="vp8,
  vorbis"' />
•   <source src="movie.ogv" type='video/ogg; codecs="theora,
  vorbis"' />
• </video>

```

The full level of integration of the video tag as a native browser element deprecates issues that might arise with third party embedded players such as drop down menus and iframes overlaying on the player or weird layout behaviour when the other HTML elements surrounding the video were dynamically resized.

Since the video is not treated as an embedded foreign object, there are some other benefits that affect the user experience. For instance, even if the focus is on the player itself actions like page scrolling or keyboard key strokes will be completely functional.

▶ VIDEO + JS

The video tag comes with a set of attributes and methods which let you have a fine control of your video from your JS code. As any other HTML element you can attach common events to the video tag such as drag events, mouse events, and focus events. Since loading a video resource can have many caveats, there are many events to have a fine control of the loading process, both at network level (loadstart, progress, suspend, abort, error, emptied, stalled) and at buffering level (loadedmetadata, loadeddata, waiting, playing, canplay, canplaythrough).

At its simplest level, you can attach the canplay event to start doing stuff with the video.

```

• video.addEventListener('canplay', function(e) {
•   this.volume = 0.4;

```