

use the spanning incognito behavior. If you want to run your app independently in an incognito window, use the split behavior.

key

Your key controls the unique ID of an extension, app, or theme when it is loaded during development. Generally, you don't need to use this you can develop your code in such a way that this would not matter. Eg. using relative paths and `chrome.extension.getURL()`.

To get a suitable key value, first install your extension from a .crx file (you may need to upload your extension or package it manually). Then, in your user data directory, look in the file `Default/Extensions/<extensionId>/<versionString>/manifest.json`. You will see the key value filled in there.

minimum_chrome_version

This is used to specify the version of Chrome that your extension, app, or theme requires to run. The format for this string is the same as for the version field.

permissions

We have an idea of what permissions from a user's perspective. Now let's look at the developer side of permissions. Permissions will allow you to access a user's data which is critical to the function of any app. An app may use a single or an array of permissions depending on its requirements. Each permission can be either one of a list of known strings (such as "geolocation") or a match pattern that gives access to one or more hosts. Any permission that you use is displayed to the user before he installs the app.

Here's an example of the permissions part of a manifest file for an extension:

```
• "permissions": [
•   "geolocation",
•   "bookmarks",
•   "notifications",
•   "http://*.google.com/",
•   "unlimitedStorage"
• ],
```

The following table lists the permissions an extension or packaged app can use.

Notes

Hosted apps can use the "background", "geolocation", "notifications", and "unlimitedStorage" permissions, but not any other permissions listed in this table.