

browser action

browser actions can be used to put an icon, tooltip, badge and pop ups in Google Chrome. Packaged apps cannot use browser actions.

A browser action in your manifest will look something like this:

```
• {
•   "name": "cool app name",
•   ...
•   "browser_action": {
•     "default_icon": "images/image001.png", // optional
•     "default_title": "ThinkDigit",        // tooltip,
optional
•     "default_popup": "popup.html"         // optional
•   },
•   ...
• }
```

Icon: icons can be up to 19 pixels wide and high. Any larger icons will be resized to fit, so use the mentioned icon size for best results. Images can be in BMP, GIF, ICO, JPEG, or PNG i.e. any format WebKit can display. You can have animated UIs using the canvas element.

To set the icon, use the `default_icon` field of `browser_action` in the manifest, or call the `setIcon()` method.

`chrome.browserAction.setIcon(object details)`

Tooltip: to set the tooltip, use the `default_title` field of `browser_action` in the manifest, or call the `setTitle()` method. You can specify locale-specific strings for the `default_title` field; see Internationalization for details.

Badge: you can choose your browser action to optionally display a badge which is a bit of text that is layered over the icon. Badges make it easy to update the browser action to display a small amount of information about the state of the extension. You should display the information in 4 characters or less because of the limited space if the badge.

Set the text and color of the badge using `setBadgeText()` and `setBadgeBackgroundColor()`, respectively.

Popup: Including this browser action in your manifest would make a popup appear when the user clicks the icon. This new popup can contain any HTML contents that you like which will be automatically sized to fit its contents.

To add a popup to your browser action, create an HTML file with the popup's contents. Specify the HTML file in the `default_popup` field of