

```

•   },
•   "colors" : {
•     "frame" : [71, 105, 91],
•     "toolbar" : [207, 221, 192],
•     "ntp_text" : [20, 40, 0],
•     "ntp_link" : [36, 70, 0],
•     "ntp_section" : [207, 221, 192],
•     "button_background" : [255, 255, 255]
•   },
•   "tints" : {
•     "buttons" : [0.33, 0.5, 0.47]
•   },
•   "properties" : {
•     "ntp_background_alignment" : "bottom"
•   }
• }
• }

```

Colours: Colours are in the standard RGB format. To find the strings you can use within the “colors” field, look for `kColor*` strings in `theme_service.cc`.

Images: Image resources use paths relative to the root of the extension.

Properties: This field lets you specify properties such as background alignment, background repeat, and an alternate logo.

Tints: You can specify tints to be applied to parts of the UI such as buttons, the frame, and the background tab. As of now, Google Chrome supports tints, not images, because images don’t work across platforms.

Tints are in Hue-Saturation-Lightness (HSL) format, using floating-point numbers in the range 0 - 1.0. Hue is an absolute value, with 0 and 1 being red. Saturation is relative to the currently provided image. 0.5 is no change, 0 is totally desaturated, and 1 is full saturation. Lightness is also relative, with 0.5 being no change, 0 as all pixels black, and 1 as all pixels white.

You can alternatively use -1.0 for any of the HSL values to specify no change.

Background page

You often have the need to have a single long-running script to manage some task or state. This is where background page comes to the rescue. This HTML page runs in the extension process. It runs as long as the app is running and only one instance is active at any given time.