

Since incognito windows run independently, you cannot override the New Tab pages cannot be overridden in incognito windows. You can override other pages in the incognito window by setting the incognito manifest property to spanning..

Override your new page

- `{// substitute the new page`
- `"name": "cool extension",`
- `...`
- `"chrome_url_overrides" : {`
- `"newpage": "myPage.html"`
- `},`
- `...`
- `}`

You can also have bookmarks or history in place of newpage.

While designing override pages, remember 2 things

Quick load: No user likes to wait, that too for a built in browser pages.

Do not set up any process that would take time loading

Title: The user can get confused by seeing the URL of your page. Keep it simple and clear.

NPAPI plugins

Warning: only use this when every other way does not work.

HTML and JavaScript are a great help in developing new extensions, but what if you wanted you use an existing code? Bundling an NPAPI plugin with your extension will allow you to call into native binary code from JavaScript. The administrator runs the binary code, so it runs with administrator privileges.

Any code that runs in an NPAPI plugin has the full permissions of the current user and so he is exposed to malicious input since he is no more shielded by Google Chrome in any way. You should be especially cautious when processing input from untrusted sources, such as when working with content scripts or XML[HttpRequest](#).

Extensions that use the NPAPI plugin will be manually reviewed before they can be published

After you've got an NPAPI plugin (See Mozilla's NPAPI plugin reference for information on how to do that), follow these steps to get your extension using it.