

```

    $this->consumer = new OAuthConsumer(
        self::CONSUMER_KEY, self::CONSUMER_SECRET,
        NULL);
    $this->token = new OAuthToken(self::TOKEN,
        self::TOKEN_SECRET);
    $this->signatureMethod = new OAuthSignatureMethod_
        HMAC_SHA1();
    }

```

\$url stores the complete URL that points to the resource that needs to be accessed.

\$request is used to contain the signed request that is to be made to the resource.

\$extraHeadervariable stores any additional headers that might be required.

\$returnResponseHeaders is set to True if the response headers are to be returned, else it is False.

```

    protected function send_signed_get($request,
        $extraHeaders=NULL,
        $returnRequestHeaders=false,
        $returnResponseHeaders=false) {
        $url = explode('?', $request->to_url());

```

Curl is a tool to transfer data to or from server, similar to wget. It supports a wide range of protocols. In the code below, the curl library customises various options of the connection.

```

    $curl = curl_init($url[0]); // starting a curl session to
    create a url
    curl_setopt($curl, CURLOPT_RETURNTRANSFER, true);
    curl_setopt($curl, CURLOPT_FAILONERROR, false);
    curl_setopt($curl, CURLOPT_SSL_VERIFYPEER, false);

```

The request headers here are sent back in the response

```

    curl_setopt($curl, CURLINFO_HEADER_OUT, $returnRe-
        questHeaders);

```

As mentioned above, if we want the response headers, this property can be changed.