

```

• if ($returnResponseHeaders) {
•   curl_setopt($curl, CURLOPT_HEADER, true);
• }

```

Any extra headers if present are appended to the headers

```

•   $headers = array($request->to_header());
• if (is_array($extraHeaders)) {
•   $headers = array_merge($headers, $extraHeaders);
• }
• curl_setopt($curl, CURLOPT_HTTPHEADER, $headers);

```

After setting all the options like the destination url, the appropriate headers, we now send the request to the authentication server by issuing `curl_exec()`. In case of a response, it is stored.

```

•   // Execute the request. If an error occurs fill the
response body with it.
•   $response = curl_exec($curl);
• if (!$response) {
•   $response = curl_error($curl);
• }
•
•   // Add server's response headers to our response body
•   $response = curl_getinfo($curl, CURLINFO_HEADER_OUT)
. $response;
• curl_close($curl);
•
• return $response;
• }

```

The response returned may be either the desired one or an error message, depending upon the request sent to the authentication server resource.

The function below, as its name suggests, checks the licence given the userID of the user:

```

• public function checkLicense($userId) {
•   $url = self::LICENSE_SERVER_HOST . '/chromewebstore/
vl/licenses/' .
•       self::APP_ID . '/' . urlencode($userId);
•
•   $request = OAuthRequest::from_consumer_and_token(
•       $this->consumer, $this->token, 'GET', $url, array());

```