


- `</s:stroke>`
- `</s:Ellipse>`
- `</s:Application>`


The fill property contains an array of GradientEntry objects. Each can be assigned a ratio value from 0 to 1 that determines where in the graphical element the colour change occurs. The following Path object uses a RadialGradient with many instances of the GradientEntry class. They alternate colours and determine where the colours change in the graphical element with their ratio values:

```
<s:Path data="M 0 40 L 40 0 L 105 0 L 144 40 L 144 51 L 105 90 L 40 90 L 0 51 L 0 40 Z ">
  <s:fill>
    <s:RadialGradient>
      <s:GradientEntry color="#333333" ratio="0" alpha="1"/>
      <s:GradientEntry color="#CCCCCC" ratio="0.09" alpha="1"/>
      <s:GradientEntry color="#333333" ratio="0.37" alpha="1"/>
      <s:GradientEntry color="#CCCCCC" ratio="0.89" alpha="1"/>
      <s:GradientEntry color="#333333" ratio="0.99" alpha="1"/>
    </s:RadialGradient>
  </s:fill>
</s:Path>
```

The result: a symmetrical polygon with a series of concentric radial gradients. A symmetrical polygon with a radial gradient fill defined with primitive vector graphic classes declared in MXML



Visual result: two Ellipse objects with different types of gradient fills. These ellipse objects use, respectively, a linear and a radial gradient fill



Reusing graphic elements with `<fx:Library>` and `<fx:Definition>`

The Flex SDK now has a new MXML element named `<fx:Library>` that you use to define graphic elements that can then be reused anywhere in the same MXML document. Within the `<fx:Library>` element, you define one or more `<fx:Definition>` element. Each `<fx:Definition>` describes a graphic