

element. Note, the `<fx:Library>` tag must be placed as the first child element within the MXML document's root element. If you place any other tags before it, a compiler error is generated. The application `CurvedArrow` below defines a single vector graphic as a library definition. In the body of the application, there are three instances of the graphic. Each sets its `scaleX` and `scaleY` properties to a different value. The resulting application displays three instances of the arrow. Even though they're different sizes, they all show clean curves and smooth gradient fills.

A library definition shape used multiple times

```
<?xml version="1.0" encoding="utf-8"?>
<s:Application xmlns:fx="http://ns.adobe.com/mxml/2009"
  xmlns:s="library://ns.adobe.com/flex/spark">
  <fx:Library>
    <fx:Definition name="CurvedArrow">
      <s:Path data="M 20 0
        C 50 0 50 35 20 35
        L 15 35 L 15 45
        L 0 32 L 15 19
        L 15 29 L 20 29
        C 44 29 44 6 20 6"/>
      <s:stroke>
        <s:SolidColorStroke color="0x888888"/>
      </s:stroke>
      <s:fill>
        <s:LinearGradient rotation="90">
          <s:GradientEntry color="0x000000" alpha="0.8"/>
          <s:GradientEntry color="0xFFFFFF" alpha="0.8"/>
        </s:LinearGradient>
      </s:fill>
    </s:Path>
  </fx:Definition>
</fx:Library>
<s:HGroup horizontalCenter="0" top="20">
  <fx:CurvedArrow scaleX="1" scaleY="1"/>
  <fx:CurvedArrow scaleX="2" scaleY="2"/>
  <fx:CurvedArrow scaleX="4" scaleY="4"/>
</s:HGroup>
</s:Application>
```

The `<fx:Library>` MXML tag is new in Flex. You use it to define reusable graphic elements. Each reusable graphical element is defined in